

#### **COCHIN PORT TRUST**

#### COCHIN-682009, KERALA, INDIA

Tele: 91-0484-2666414, 2666871

Telefax: 91-0484-2666414

E-mail:coptce@gmail.com

# TENDER DOCUMENT FOR DEMOLISHING AND RE CONSTRUCTION OF TOILET & OFFICE ROOM FOR CISF, COPT AND BPCL AT COT (Retender).

TECHNICAL BID (e-Tendering Mode)

Website:www.tenderwizard.com/CoPT

**CHIEF ENGINEER'S OFFICE** 

**COCHIN PORT TRUST** 

**COCHIN-682009** 

TENDER No.T6/T-1909/2019-C

**PRICE: Rs.788/-**

#### **COCHIN PORT TRUST**

# TENDER FOR 'DEMOLISHING AND RE CONSTRUCTION OF TOILET & OFFICE ROOM FOR CISF, COPT AND BPCL AT COT' (Retender) (Tender No.T6/T-1909/2019-C)

#### **CONTENTS**

| S1  | Items  | Page Nos. |
|-----|--|-----------|
| No: |  |           |
| 1   | Tender Notice  | 3-10      |
| 2   | Tender for Works   | 11-12     |
| 3   | Contract Data  | 13-16     |
| 4   | Instructions to Tenderers                                  | 17-21     |
| 5   | General Description and Special Conditions of Contract     | 22-30     |
| 6   | Detailed specifications for materials to be used on works  | 31-37     |
| 7   | Detailed Specifications for items of Works                 | 38-46     |
|     | General Conditions of Contract-2016. (Attached Separately) |           |

SIGNATURE OF TENDERER

#### **COCHIN PORT TRUST**

#### CHIEF ENGINEER'S OFFICE, COCHIN – 682009

No.T6/T-1909/2019-C Dated:-19/12/2019

#### 1. TENDER NOTICE

1.1 Electronic tenders (e-tenders) in "Two Cover System" for "Demolishing and re construction of toilet & office room for CISF, copt and BPCL at COT (Retender)" are invited by the Suptdg. Engineer(CM), Cochin Port Trust, Willingdon Island, Cochin- 9 and will be received up to 14.30hrs. on 01/01/2020. The tenders shall be submitted in accordance with the 'Instruction to Tenderers' and 'General Description and Special Conditions of Contract' etc. as detailed in the Tender Documents. The tenders will be opened by the Chief Engineer, Cochin Port Trust at this office on the same day at 15.00 hrs.

#### **Estimated cost:15,76,500/-**

- 1.2 The Tender Document can be down loaded from the e-tendering portal <a href="https://www.tenderwizard.com/COPT from 10.00hrs.on 19/12/2019">www.tenderwizard.com/COPT from 10.00hrs.on 19/12/2019</a> to 14.30hrs on 01/01/2020 by making online requisition & submission of Demand Draft/Banker's Cheque for Rs.750/-+GST @5%(ie, Rs.788/-) drawn in favour of the FA & CAO, Cochin Port Trust, payable at Kochi, being the cost of single copy of the Tender Document. Scanned copy of the DD/ Banker's Cheque shall be attached with the e-tender.
- 1.3 The Tender Documents are also available at Port's website **www.cochinport.gov.in** or Government of India CPP portal for reference.
- 1.4 The bidders need to obtain the one time User ID & password for log-in to e-Tendering Portal <a href="www.tenderwizard.com/COPT">www.tenderwizard.com/COPT</a> from the service provider M/s.KEONICS by paying registration amount of Rs.1124/- through online Payment using Credit/Debit Card/Net banking or DD in favour of "KSEDCL, Bangalore".
- 1.5 The tender shall be submitted by an individual or by a registered Partnership firm or by a Limited Company. In the event of the tender being submitted by a registered partnership firm, it must be signed individually by each partner thereof. In the event of absence of any partner, it must be signed on his behalf by the person holding a proper power-of-attorney, authorizing him to do so and to bind the partner in all matters pertaining to the Contract including the arbitration clause, such power-of-attorney to be attached with the tender which must disclose that the firm is duly registered under Indian Partnership Act. If the tender is made by a Limited Company it shall be signed by a duly authorised person who shall produce with the tender satisfactory evidence of

the authorization. In the case of a Limited Company the tender should be accompanied by the Memorandum and Articles of Association of the Company. **Joint Venture is not allowed in the tender.** 

- 1.6 The tenders shall be submitted "on line" strictly in accordance with the Instructions to Tenderers and General Description and Special Conditions of Contract given in the Tender Document. The bidders shall submit scanned copy of all the required documents such as DD / Bankers Cheque towards the cost of tender form and EMD; proof of experience, financial details, etc. along with e-tenders.
- 1.7 Original DD / Bankers Cheque towards the cost of tender and EMD, shall be submitted in a sealed cover to the **Suptdg. Engineer (CM), Cochin Port Trust, W/Island, Cochin-682009, KERALA,** before opening date & time of the tender. **Tenders without submitting the original documents as above, shall be liable for rejection.**
- 1.8 The intending bidder must have valid Class-II or III digital signature certificate to submit the bid. For further details, please contact e-Tender Help Desk No. 080-40482000/9746118529/9605557738.

#### 1.9 EARNEST MONEY TO BE DEPOSITED

1.9.1 Each tender should be accompanied by an Earnest Money amounting to Rs.15,770/-. The Earnest Money can be deposited through Demand Draft or Banker's Cheque or Pay Order from a Scheduled Bank in India, drawn in favour of Financial Adviser & Chief Accounts Officer, Cochin Port Trust. The original DD/Banker's Cheque/ Pay Order shall be submitted to the Chief Engineer/ Dy.CE/SE, Cochin Port Trust, Cochin – 9, before opening time of the tender. Scanned copy of the DD/ Banker's Cheque/ Pay Order shall be attached with the tender submitted "online". The Earnest Money deposited will not carry any interest.

#### 1.10 Tender Submission/Opening:

1.10.1 The time schedule for various activities in connection with this tender will be as follows.

| Description of activity                      | Schedule time           | Venue                   |
|--|-------------------------|-------------------------|
| a)Last date & time for submission of tenders | 14.30 hrs on 01/01/2020 |                         |
| b)Public opening of<br>Tenders               | 15.00 hrs on 01/01/2020 | Chief Engineer's Office |

1.10.2 Tender shall include Cover A containing hard copy of "EMD & COST OF TEDNER FORM". All other technical details including Technical Bid & Price Bid shall be submitted only online.

1.10.3 The Officer opening the Cover A-containing the "EMD & COST OF TENDER FORM" shall first open. Technical Bid of only those tenderers shall be opened, whose documents furnished in the Cover A, are found to be in order. Others will not be opened; Only a mention to this effect shall be made in the tender opening register.

# 1.10.5 Technical Bid & Price Bid shall be submitted only 'Online'. The name and address of the tenderer shall be necessarily entered in the space provided in 'Price Bid'.

- 1.11 The right of acceptance of tender will rest with Port Trust Board who does not bind themselves to accept the lowest tender and reserves to themselves the authority to reject any or all of the tenders received without assigning any reason.
- 1.12 The Chief Engineer/ Dy. CE/ Suptdg. Engineer or his duly authorized assistant will open the tenders in the presence of intending tenderers who may be present at the time in person or through their authorized representative. In the event of a tender being rejected, the Earnest Money paid with such unaccepted tender shall be refunded to the tenderer by the Financial Adviser and Chief Accounts Officer direct.
- 1.13 i) The tenderer should keep open the validity of the tender normally for 60 days from the date fixed for its opening. However, it is also obligatory for the tenderer to keep the validity open for another 60 days for which request in writing/ telefax/e-mail by the Chief Engineer before the expiry of the original validity would be sufficient intimation. The receipt of the intimation of the Chief Engineer should be acknowledged.
  - ii) Should any tenderer withdraw his tender before these periods, or make any modification in the terms and conditions of the tender which are not acceptable to the department, the Earnest Money deposited by the tenderer shall be forfeited.
- 1.14 The tenderer shall visit the site of work in order to acquaint himself with the conditions of the site, the locality and its environment.
- 1.15 The tenderer shall be deemed to have full knowledge of all documents, site, etc. whether he has inspected them or not. The submission of a tender by tenderer implies that he has read this notice and General Conditions of Contract and has made himself aware of the scope and specifications and other factors bearing on the tender.

#### 1.16 Securities:

1.16.1 Security Deposit (SD) shall be 10% of the Contract value or value of the work done whichever is higher and it shall consist of the following two parts:

- a) **Performance Security** payable on award of the work.
- b) **Retention Money** to be recovered from Running Bills as detailed in Clause 48 of GCC.

The total amount thus deposited towards SD will be retained as security for the due and proper fulfillment of the Contract and will not carry any interest. Such deposit shall be forfeited on failure to perform or non-fulfillment by the Contractor of the terms and conditions of the Contract.

- 1.16.2 **Performance Security:** The Performance Security retained till end of Defects Liability Period shall be 5% of Contract Value or Cost of Work Done, whichever is higher. So, initially 5% of the Contract value shall be furnished as Performance Security.
- 1.16.3 The Performance Security shall be provided by the Contractor to the Employer not later than **14 days** from the date of receipt of work order and shall be furnished in one of the following forms:
  - i) Banker's Cheque/Demand Draft/Pay Order of a Scheduled Bank.
  - ii) An irrevocable Bank Guarantee(BG) enforceable and encashable at Cochin, drawn from any Scheduled Bank operating in India as per the prescribed proforma.
- 1.16.4 The BG furnished towards the Performance Security shall be valid until a date 30 days from the day of expiry of the Defect Liability Period stipulated as per the terms of the Contract.
- 1.16.5 Unless Performance Security is furnished within the period as specified above or such extension of that period as may be permitted by the Engineer in writing, the Earnest Money will be liable to forfeiture and the Contract to cancellation.
- 1.16.6 Performance Security will be released / refunded to the Contractor not later than 30 days from the date of completion of Defect Liability / Warranty Period of the work.
- 1.16.7 **Retention Money:** Retention Money @ 5% shall be retained from each payment due to the Contractor.
- 1.16.8 Retention Money shall be deducted at 5% of the gross amount of the bill from the first Running Account bill onwards till the recovered sum alongwith Performance Security amounts to 10% of the Contract value or the value of the work done whichever is higher at all times. Retention Money shall be refunded to the Contractor within 14 days from the date of payment of final bill.
- 1.16.9 The Performance Security retained till end of Defect Liability Period shall be 5% of Contract Value or Cost of Work Done, whichever is higher.

- 1.16.10 If the Cost of Work done exceeds the Contract Value, the total amount retained as Security Deposit considering the Performance Security initially submitted together with the Retention Money recovered from the running account bills, shall amount to 10% of the Cost of Work done.
- 1.16.11 In cases where cost of Work done exceeds the Contract Value While releasing the Retention Money after payment of Final Bill, only 5% cost of Work Done is released, instead of the entire Retention Money recovered from the bills. The balance amount shall be retained to make up for the shortage in the Performance Security, upon completion of the Defects Liability Period.
- 1.17 EMD shall be refunded to the Contractor on acceptance of Performance Security and entering into agreement.
- 1.18 In the event of the tenderer, after the issue of the communication of acceptance of offer by the Board, failing /refusing to execute the agreement as hereinafter provided, the tenderer shall be deemed to have abandoned the Contract and such an act shall amount to and be construed as the Contractor's calculated and willful breach of the Contract, the cost and consequence of which shall be to the sole account of the tenderer and upon such an event, the Board shall have full right to claim damages therefore either together with or in addition to the forfeiture of Earnest Money Deposit.

#### 1.19 Signing of Agreement:

- 1.19.1 The successful tenderer will be required to execute within **21 days** from the date of receipt of work order, an agreement at his expense on proper value Kerala State Stamp Paper in the prescribed departmental form, consisting of:
  - a) The Tender Notice, all the documents including additional conditions/specifications and drawings, if any, forming the tender as issued at the time of invitation of tender and acceptance thereof together with any correspondence leading there to, and
  - b) General Conditions of Contract-2016 (GCC), for the due and proper fulfillment of the Contract.
- 1.19.2 The Contractor shall make 10 copies of the Agreement and submit to CoPT within 7 days following the date of signing of Agreement.
- 1.20 Till signing of agreement the tender together with the acceptance letter shall constitute a binding Contract between the Contractor and Cochin Port.
- 1.21 Failure to comply with conditions **1.13**, **1.16 and 1.19** above will entail forfeiture of the Earnest Money.
- 1.22 Tenders received shall be considered for acceptance, only if it meet the Minimum Qualification Criteria stipulated below:

#### **Minimum Qualification criteria required for considering tenders:**

#### (i) <u>Experience:</u>

The tenderer should have successfully completed at least:

one similar work of value not less than Rs.12.61 lakhs OR

two similar works, each of value not less than Rs.7.88 lakhs OR

three similar works, each of value not less than Rs.6.31 lakhs, during the preceding seven years ending 31st August 2019.

#### **Explanatory notes:**

- (a) Similar work(s) means "Civil construction works".
- (b) The experience certificate of works executed in private sectors/organizations, shall be considered for qualification, only on submission of TDS certificate along with work order and completion certificate.
- (c) Copy of completion certificates of each work issued by the owner/responsible officer of the owner under whom he has executed such contract shall be attached. The certificate shall contain details of work involved specifying the nature of work, the completion cost of the work, date of commencement & date of completion of the work.
- (d) The works reckoned for the above purpose are those executed by the tenderers as prime Contractor or proportionately as member of joint venture or sub Contractor. The subcontractor shall be an authorized and approved sub-Contractor by the Employer of the work(s) against which the tenderer has claimed his experience. The tenderer shall attach attested copy(s) of approval issued by the Employer(s) authorizing as a sub-Contractor; in proof of the claim of the tenderer as a sub-Contractor. The tenderer is also obliged to produce the original of the certified copy(s) on request by the department.
- (e) Following enhancement factors will be used for the costs of works executed for bringing the financial figures to a common base value in respect of the works completed in the past years.

| Year before | Multiplying factor |
|-------------|--------------------|
| One year    | 1.07               |

| Two years   | 1.14 |
|-------------|------|
| Three years | 1.21 |
| Four years  | 1.28 |
| Five years  | 1.35 |
| Six years   | 1.42 |

#### (ii) <u>Financial Turnover:</u>

Average Annual Turnover of the tenderer during the last three financial years ending 31<sup>st</sup> March 2019 shall not be less than Rs.4.73 Lakhs.

In proof of this Audited Annual Accounts Statements or IT returns duly acknowledged by the Income Tax department along with computation statement signed by the Auditor/ Chartered Accountant, for the last three years shall be produced by the tenderer.

- 1.23 Tenders which do not fulfill all or any of the above conditions or which contain any other condition of any sort including conditional rebates or are incomplete in any respect is liable for rejection. Such tenders shall be entered in the tender opening register but their rates shall neither be read out nor entered in the register. Only remark mentioning the reason of rejection in brief shall be appended against such entry.
- 1.24 Canvassing in connection with tender is strictly prohibited and tenders submitted by the Contractors who resort to canvassing will be liable to rejection.
- 1.25 The tenderer shall specify the PAN No. allotted to him so that Chief Engineer/ Executive Engineer can ascertain his liability to the Income Tax Department.
- 1.26 The tenderer shall furnish documentary evidence in support of Goods & Service Tax (GST) Registration.
- 1.27 Tender Documents can be seen at Chief Engineer's Office during working hours on all days except on Sundays, second and fourth Saturdays and Public Holidays.

#### 1.28 Taxes and Duties:

- 1.28.1 Deductions towards statutory taxes as per the rules, prevailing in force at the time of payment of bills shall be made while releasing the bill amount.
- 1.28.2.GST for the work will be paid extra by the Port. The GST applicable as per law can be billed on the Port Trust, which will be paid to the Contractor by the

Board along with the bills, for which the Contractor holds valid GST Registration number and the GST is being collected. The following are also to be considered while claiming payment towards GST:

- i. Invoice in specific format should be provided by the Contractor for every payment.
- ii. GST Registration Number of Cochin Port Trust and the Contractor is to be clearly mentioned with all the bills.
- iii. Invoice should be attached along with the running bills.
- iv. The Contractor shall comply all the GST regulations, viz.; timely uploading of invoices and issue of debit/ credit notes.
- 1.28.3. Any stipulation by a tenderer that taxes and duties deductable from these bills should be borne by the Port Trust will result in the summary rejection of his /their tender.
- 1.29 Cess as per Building and other Construction Workers Welfare Cess Act (Act 28 of 1996) at the rate of one percent or at the rates prevailing in force at the time of payment of bills, of the cost of construction should be borne by the Contractor and the same will be deducted from Contractor's bills while making payment or when crediting amount to Contractor's account.
- 1.30 The undersigned reserves the right to reject/cancel/postpone any one or all tenders at any stage of the tender, which will be binding on all bidders.
- 1.31 This Tender Notice shall form part of the Contract.

Chief Engineer
Cochin Port Trust
For and on behalf of the Board of Trustees of the Cochin Port Trust

#### 2. TENDER FOR WORKS

To

The Board of Trustees,

**Cochin Port Trust** 

**Through** 

The Chief Engineer

Cochin Port Trust, Cochin -9

I/We hereby tender for the execution of the work specified in the underwritten memorandum within the time specified in such memorandum at the rates specified in the schedule attached hereto and in accordance in all respects with the specifications, designs, drawings and instructions in writing referred to in 'clause 16' of the General Conditions of Contract and with such materials as are provided for, by and in all other respects in accordance with such conditions so far as applicable.

#### MEMORANDUM

General description of work : Demolishing and re construction of

toilet & office room for CISF, CoPT

and BPCL at COT.

b) Estimated cost : Rs. 15,76,500/-

c) Earnest Money : Rs.15,770/-

: 10% of the value of the Contract d) Security Deposit

> awarded or value of the work done whichever is higher. (Performance Security @ 5% and Retention Money @

5%)

from the bills

e) Percentage, if any, to be deducted: The Retention Money will be recovered

from the first running bill onwards at the rate of 5% of the gross amount of each bill. Also refer Clause 1.16 in the

Tender Notice.

Time allowed for commencement of

work from the date of receipt of: 7 days

work order

g) Time allowed for the work from the : 4 Months

date of commencement of work

| h) Schedule, specifications, conditions, : As per "Contents" sheet attached. drawings etc.   |
|--|
| Should this tender be accepted, I/We hereby agree to abide by and fulfill all the terms  |
| and provisions of the said conditions of Contract annexed here to so far as applicable or in default thereof forfeit and pay to the Board the sum of money mentioned in the said conditions and to execute an agreement with the Board in the prescribed form or in default thereof to forfeit the Earnest Money deposited by me/us. The sum of Rs |
| Signature of the Tenderer Address :  |
| Witness :  |
|  |
| Address :  |
| Occupation :   |
| ACCEPTANCE  The above tender is hereby accepted by me for and on behalf of the Board.  |
| Dated theday of2019.   |
| Dated  |
| Chief Engineer   |
| Cochin Port Trust  |

### 3. CONTRACT DATA

#### Items marked "N/A" do not apply in this Contract.

| Sl.<br>No. | Description   |             |            | Reference<br>Cl.No. of<br>GCC |       |
|------------|---|-------------|------------|-------------------------------|-------|
| 1          | The following documents are also part of the Contract                       |             |            |                               |       |
|            | The Schedule  |             |            |                               | (8.2) |
|            | i)  |             |            |                               | N.A   |
|            | The Schedule  | of Key pers | sonnel     |                               | (9)   |
|            | Qualification   | No.         | Min.       | Rate of                       | N.A   |
|            | of Staff  |             | Experience | recovery in                   |       |
|            |   |             | (Years)    | case of non-                  |       |
|            |   |             |            | compliance                    |       |
|            | Graduate  |             |            | Rs.15,000/-                   |       |
|            | Engineer  | 1           | 2          | p.m                           |       |
|            | or  |             |            | ρ                             |       |
|            | Diploma   |             |            | Rs.15,000/-                   |       |
|            | Engineer  | 1           | 5          | p.m                           |       |
|            | Liigiileei  |             |            | P.III                         |       |
| 2          | The Employer  | is          |            |                               | (1)   |
|            | The Board of Trustees,<br>Cochin Port Trust,<br>Cochin -9                   |             |            |                               |       |
|            | Name of Authorized Representative:  |             |            |                               |       |
|            | Name: Dr. M. Beena,   |             |            |                               |       |
|            | Chairperson,<br>Cochin Port Trust,  |             |            |                               |       |
|            |   | chin -9.    | 1 450,     |                               |       |
| 3          | The Engineer is:  |             |            |                               |       |
|            | Name: Shri. G. Vaidyanathan,  |             |            |                               |       |
|            |   | ief Enginee | ,          |                               |       |
|            | Cochin Port Trust,  |             |            |                               |       |
|            | Cochin-9.   |             |            |                               |       |
|            | The Nominee/ Engineer-in-Charge is:  Name: Smt C S Pokha Eva Engineer(CM I) |             |            |                               |       |
|            | Name: Smt. C.S.Rekha, Exe. Engineer(CM-I)                                   |             |            |                               |       |
| 4          | Name of Contract: "Demolishing and re construction of                       |             |            | construction of               | (1)   |
|            | toilet & office room for CISF, CoPT and BPCL at COT                         |             |            |                               |       |
|            | (Retender). Tender No: T6/T-1909/2019-C                                     |             |            |                               |       |
| 5          | 10 copies of Contract Agreement shall be furnished by                       |             |            |                               |       |

| Sl.<br>No. | Description   |   | Reference<br>Cl.No. of<br>GCC |
|------------|---|---|-------------------------------|
|            | the Contractor  |   | [7.1]                         |
| 6          | Tender Document and other d Chief Engineer's Office,  | ata are available at :  | (7.2)                         |
|            | Cochin Port Trust, W/Island   | <b>l</b> ,  |                               |
|            | Cochin – 682009, KERALA   |   |                               |
| 7          | The Intended Completion Da Work is <b>4 months</b> with the   |   | (17.28)                       |
| 8          | Milestone dates:  |   |                               |
|            | Physical works to be completed  | Period from the date of receipt of LoA to proceed with the work |                               |
|            | 4 months  | 7 days  |                               |
| 9          | The following shall form part of the Contract Document:  (1) Form of Agreement  (2) Letter of Acceptance (3) Contractor's Bid (4) Contract Data (5) General Conditions of Contract (GCC) (6) Instructions to Tenderers (7) General Description and Special Conditions of Contract (8) Detailed Specifications for Materials and Works (9) Drawings (if any) (10) Schedule of quantities and (11) Any other documents listed in the Contract Data as forming part of the Contract. (12) Correspondence exchanged after the opening of the Bid and before the issue of Letter of Acceptance by which the Condition of Contract are amended, varied or modified in any way by mutual consent |   |                               |
| 10         | The Contractor shall submit within <b>7 (Seven) days</b> of day Acceptance.   | _   | (27)                          |
| 11         | The site possession date:   | within 7 (Seven) days after                                     | (21)                          |

| Sl.<br>No. | Description  | Reference<br>Cl.No. of<br>GCC |
|------------|--|-------------------------------|
|            | receipt of LoA and the site is free from encumbrances.   |                               |
| 12         | The Start Date shall be within <b>7</b> ( <b>Seven</b> ) <b>days</b> from the date of receipt of the Letter of Acceptance (LoA) by the Contractor.   | (1)                           |
| 13         | The site is located at W/ Island   |                               |
| 14         | The Defects Liability Period is : One year from the date of completion of work.  | (35)                          |
| 15         | The minimum insurance cover for physical property, injury and death is <b>Rs.10 lakhs</b> ( <b>Rupees Ten lakhs</b> ) per occurrence with the number of occurrences unlimited. After each occurrence, Contractor will pay additional premium necessary to make insurance valid always. | (13)                          |
| 16         | The following events shall also be Compensation Events:  | (44)<br><b>N/A</b>            |
| 17         | The period between Programme updates shall be <b>30 days</b>   | (27)                          |
| 18         | The amount to be with held for late submission of an updated Programme shall be Rs   | (27)<br>N/A                   |
| 19         | The language of the Contract documents is <b>English.</b>  | (3)                           |
| 20         | The law, which applies to the Contract, is the law of Union of India.  | (3)                           |
| 21         | The currency of the Contract is <b>Indian Rupees.</b>  | (46)                          |
| 22         | The proportion of payments retained (Retention Money) shall be 5% from each bill subject to a maximum of 5% of the Contract price or value of the work done whichever is higher.   | (48)                          |
| 23         | The maximum amount of Liquidated Damages for the whole of the works is 10% of the Contract Price.  | [49]                          |
| 24         | The amounts of the advance payments: The advance payments as applicable to the Contract are:   | [51]<br><b>N</b> /A           |
| 25         | Repayment of advance payment for mobilization:   | [51] <b>N/A</b>               |
| 26         | Repayment of advance payment for Construction and  | [51]                          |
|            | Equipment:   | N/A                           |
| 27         | Repayment of Secured Advance:  | N/A                           |
| 28         | The date by which "As Built Drawings" are required is within days of issue of certificate of completion of whole or section of the work, as the case may be.   | (58)<br><b>N/A</b>            |

| Sl.<br>No. | Description   | Reference<br>Cl.No. of<br>GCC |
|------------|---|-------------------------------|
| 29         | The amount to be withheld for failing to supply "As Built               | (58)                          |
|            | Drawings" and/or operating and maintenance manuals by                   | N/A                           |
|            | the date required is Rs (Rupees)  |                               |
| 30         | Schedule of Rates Applicable: CPWD DSR 2016 + 46.08% Cost Index (-) 12% |                               |
| 31         | Base Rate for materials to be considered for price variation            | (47)                          |
| (i)        | Cement consumed for various items of work :                             | N/A                           |
| (-)        | Rs per tonne  | > """                         |
| (ii)       | Reinforcement steel used under various items :                          |                               |
|            | Rs per tonne  |                               |
| (iii)      | Structural Steel used under various items: Rs per                       | )                             |
|            | tonne   |                               |
| (iv)       | Bitumen under various items in: Rs per tonne                            | >                             |
| (v)        | Bitumen Emulsion (MS&RS) under various items in:                        | J                             |
|            | Rs per tonne  |                               |
| 32         | Permissible wastage on theoretical quantities of                        | $\rightarrow$ (47)            |
|            | (a) Cement : 2%   |                               |
|            | (b) Steel Reinforcement and   |                               |
|            | structural steel sections   | >                             |
|            | for each diameter, section<br>and category : 5.99%                      |                               |
|            | and category : 5.99% (c) Bitumen/Bitumen Emulsion : 2.5%                | J                             |
|            | (C) Ditument Ditumen Emulsion . 2.370                                   |                               |

#### 4. INSTRUCTIONS TO TENDERERS

- 4.1 Electronic Tenders (e-tenders) on percentage basis under "Two Cover system" are invited for "Demolishing and re construction of toilet & office room for CISF, CoPT and BPCL at COT (Retender)." The tenderer shall submit the tender Cover-A (Hard Copy of EMD & Cost of Tender form). All the Technical Bid documents & Price Bid shall be submitted "online".
- 4.2 The Tender Document will be available as three separate files in the etendering Portal:
  - i. A. Technical Bid Documents (as per Sl. No 1 to 7 of the Contents sheet)
  - ii. B. Price Bid: Schedule of quantities of Work- Schedule-A and
  - iii. C. General Conditions of Contract-2016
- 4.3 The tenderer shall upload the documents indicated in 4.2 (i) & (iii) above and also the Schedule of Quantities(Percentage) [as per Cl.4.3(ii), duly filled in, "online".

#### 4.4 SUBMISSION OF TENDERS

4.5.1 The Cover A shall contain – hard copy of EMD as described in Clause 1.9.1 of Tender Notice & Cost of Tender form as mentioned in Clause 1.2 of Tender Notice shall be submitted before **15.00 Hrs on 01/01/2020.** 

#### 4.5.2 Technical Bid (Online mode)

Technical Bid shall contain all technical and commercial details except Schedule of Quantities. It shall consist scanned/ soft copies of the following documents.

- a) A covering letter from the tenderer enlisting the enclosures/ attachments.
- b) Original Tender Document (Technical Bid) except Schedule of Quantities.
- c) Copy of the documents in proof of fulfillment of the Minimum Qualification Criteria.
- d) Copy of PAN Card, ESI/EPF & GST Registration documents.
- e) Copy of Authorisation documents of Signatory of the bid in case of Registered Partnership firm / Limited company
- f) Partnership deed or Memorandum and Article of Association of the company and registration certificate of the company as the case may be.
- g) Any other relevant document.

- 4.5.2.3 Scanned copies of all documents as per Clause 4.5.2, EMD and Cost of Tender Form shall be submitted as "Technical Bid".
- 4.5.2.4 Departmental Tender Document (except Schedule of Quantities), along with scanned copies of Cost of Tender form, EMD and other documents as per Clause 4.5.2 shall be submitted 'online' before 14.30 hrs of opening date of the Tender. In no case shall filled in Price Bid Schedule of Quantities be submitted in hard copy, as it shall result in rejection of the tender.

#### **4.5.3 Price Bid:**

- **4.5.3.1** Price Bid shall contain only the "Schedule of Quantities", which shall be submitted only in e-tendering mode.
- 4.5.3.2 Tenderer should ensure that his tendered percentage as per 'Price Bid' is not mentioned anywhere in any other documents, directly or indirectly. If any such mention is made, the tender will become invalid and shall become liable for rejection.
- 4.5.3.3 Tenderer shall quote the percentage in figures with Above/Below the departmental rate in the last page of Price Bid, where space provided.

#### 4.6 PRE-QUALIFICATION CRITERIA

4.6.1. Selection criteria for qualifying the tenderers for opening the Price Bids in Cover 'B' of the tender will be as below:

#### (i) Experience :

The tenderer should have successfully completed at least one similar work of value not less than Rs.12.61 lakhs

OR

two similar works, each of value not less than Rs.7.88 lakhs

OR

three similar works, each of value not less than Rs.6.31 lakhs, during the preceding seven years ending 31<sup>st</sup> October 2019.

#### **Explanatory notes:**

- a) Similar work(s) means "Civil construction works".
- b) Copy of completion certificates of each work issued by the owner/responsible officer of the owner under whom he has executed such contract shall be attached. The certificate shall contain details of work involved specifying the nature of work, the completion cost of the work, date of commencement & date of completion of the work.

- c) The experience certificate of works executed in private sectors/ organisations, shall be considered for qualification, only on submission of TDS certificate along with work order and completion certificate.
- d) The works reckoned for the above purpose are those executed by the tenderers as prime Contractor or proportionately as member of joint venture or sub Contractor. The sub-Contractor shall be an authorized and approved sub-Contractor by the Employer of the work(s) against which the tenderer has claimed his experience. The tenderer shall attach attested copy(s) of approval issued by the Employer(s) authorizing as a sub-Contractor; in proof of the claim of the tenderer as a sub-Contractor. The tenderer is also obliged to produce the original of the certified copy(s) on request by the department.
- e) Following enhancement factors will be used for the costs of works executed for bringing the financial figures to a common base value in respect of the works completed in the past years.

| Year before | Multiplying factor |
|-------------|--------------------|
| One year    | 1.07               |
| Two years   | 1.14               |
| Three years | 1.21               |
| Four years  | 1.28               |
| Five years  | 1.35               |
| Six years   | 1.42               |

#### (ii) Financial Turnover:

Average Annual Turnover of the tenderer during the last three financial years ending 31<sup>st</sup> March 2019 shall not be less than Rs.4.73 Lakhs.

In proof of this Audited Annual Accounts Statements or IT returns duly acknowledged by the Income Tax department along with computation statement signed by the Auditor/ Chartered Accountant for the last three years shall be produced by the tenderer.

#### 4.7. OPENING AND EVALUATION OF TENDERS

4.7.1 Cover 'A' containing the **EMD and cost of tender form** shall be opened at **15.00 hrs. on 01/01/2020**, the last date fixed for receiving the bid, in the SE's chamber in the presence of the tenderers or their representatives as may be present. Scanned copy of EMD & Cost of Tender form submitted online also opened at 15.00 Hrs on 01/01/2020. Technical Bid documents of only those tenderers shall be opened whose documents furnished in Cover A is found in order.

4.7.2 After opening the Technical Bid documents, it shall be thoroughly checked for completeness with respect to the details stipulated to be submitted as Technical Bid by the tenderer. The Price Bid of those tenderers satisfying the tender requirements shall only be opened. The Price Bid of those tenderers who are found responsive and satisfactory on evaluation of Technical Bid documents, will be opened after bringing all tenderers to the same footing and giving notice to the short listed tenderers, on a date to be decided and intimated later.

#### 4.8 GENERAL INSTRUCTIONS TO TENDERERS

- 4.8.1 The submission of a tender by the tenderer implies that he has read the whole tender Documents including GCC-2016.
- 4.8.2 The tenderer is advised to visit and examine the site of work and its Surroundings, discuss with connected agencies and collect all necessary information on his own responsibility for preparing the tender.
- 4.8.3 The tenderer is expected to examine the Tender Documents including all conditions, specifications, forms etc and also conditions in the G.C.C. Failure to furnish the information required in the Tender Documents/ G.C.C. or submission of a tender not conforming to the requirements in every respect, is likely to result in the rejection of the tender.
- 4.8.4 The tenderer shall quote for the work on percentage basis. The departmental rate for each item of work is given in the Schedule of Quantities. The tenderer shall fill the percentage above or below the Departmental rate, in the column provided for the purpose in the Schedule.
- 4.8.5 In case of discrepancy between the specifications and the drawings, the following order of preference shall be observed:
  - a. Conditions & Specifications of tender
  - b. Drawings.
  - c. B.I.S Specifications.
  - d. Sound Engineering Practice.
- 4.8.6. If there are varying or conflicting provisions made in any document forming part of the Contract, the Chief Engineer, Cochin Port Trust, Cochin-682009 shall be the deciding authority with regard to the intention of the document which will be binding on the tenderer/ Contractor.
- 4.8.7 Any error in description, any omissions there shall not vitiate the Contract or release the Contractor from the execution of whole or any part of the works comprised therein according to specifications or from any of his obligation under the Contract.
- 4.8.8 The Chief Engineer, Cochin Port Trust shall have the right to omit or Suspend certain items of work or revise or amend the Tender. Documents at any time prior to the due date of submission of the tender. Such revisions or amendments or extensions if any, shall be communicated to all the bidders who

have downloaded the Tender Documents, in the form of an addendum by telefax /e- mail / writing. In order to afford the Bidders with reasonable time to take addendum into account, or for any other reason, the Port Trust may, at its discretion, extend the due date for submission of tender.

- 4.8.9 All payments due to the Contractor under this Contract will be made in Indian Rupees only.
- 4.8.10 Tenders received after the date specified for submission shall not be opened.
- 4.8.11 The Bank Guarantees (BGs) to be furnished by the Contractors in connection with the tender shall be sent to by the Chief Engineer, Cochin Port Trust directly by the issuing bank under registered post with AD. The Contractor shall take the responsibility of sending BGs directly to the Port Trust by the issuing bank.

SIGNATURE OF TENDERER.

# GENERAL DESCRIPTION AND SPECIAL CONDITIONS OF <u>CONTRACT</u>

#### 1. SCOPE OF WORK

- 1.1 The proposed work is for "Demolishing and re construction of toilets and office room for CISF, CoPT and BPCL at COT" (Retender). The work consists of the following:
  - Demolishing/ dismantling RCC, brick work, partitions, doors, windows etc.
  - Providing and fixing re bars for connecting reinforcement of columns to the berth.
  - Concrete work, reinforcement work etc.
  - Brick masonry work.
  - Plastering work.
  - Flooring/dadooing with vitrified tiles, Glazed tiles etc.
  - Pipe line work with various dia. CPVC pipes.
  - Providing and fixing urinal basin, wash basins etc.
  - Aluminiun door works.
  - Painting work with cement primer, Acrylic smooth exterior/interior paints.
- 1.2 The work shall be meticulously planned in consultation with the departmental supervisory staff and nearby users, so that minimum inconvenience is caused to the functions of the wharf.

#### 2. WORK SITE

The work site is at Cochin Oil Terminal. It is a protected area of Cochin Port Trust and hence security rules and regulations including obtaining entry/ exit passes, photo passes if any for boats, men & material etc. for taking in and out the area shall be observed by the contractor at his cost.

#### 3. TIME SCHEDULE AND MONITORING OF PROGRESS

3.1 The tenderer shall prepare and attach with the tender a detailed work schedule indicating key activities and critical items for completing the work within the stipulated Contract period of **Four** months. This time schedule will form the basis for monitoring the progress of work.

#### 4. MATERIALS / FACILITIES TO BE PROVIDED BY DEPARTMENT

#### 4.1. **CONTRACTOR'S WORK AREA**

Space will be made available to the Contractor free of rent for storing materials and equipments etc., adjacent to the work site for the duration of the Contract.

After the work is over, Contractor shall at his cost, reinstate the area by clearing the temporary works, debris etc. as decided by the Engineer's Nominee.

#### 5. <u>CONTRACTOR'S RESPONSIBILITY</u>

- 5.1. The tenderer shall visit the area before tendering. It will be deemed that the tenderer has visited the site and studied the site conditions before submitting the tender. The tenderer should get himself acquainted with the nature and extent of the work. No claim whatsoever will be entertained on the plea of ignorance of difficulties involved in execution of work or carriage of materials etc.
- 5.2. All materials, plants and equipments, required for the work shall be provided by the Contractor at his own cost, and shall conform to relevant I.S. Specification unless otherwise specified.
- 5.3. Samples of all materials, to be incorporated in the work shall be got approved by the Engineer's Nominee before procurement.
- 5.4. The Contractor shall thoroughly study the specifications and errors / omissions/modifications if any shall be brought to the notice of the Engineer in-Charge well in advance so that a final decision in the matter could be given in time.
- 5.5 All labour, skilled or unskilled shall be provided by the Contractor. Settling any dispute with the labour will be Contractor's responsibility. Insurance as per Indian Workmen's Compensation Act for the Contractors' workmen and Public Liability Policy shall be provided by the Contractor at his own cost.
- 5.6. The Contractor shall be solely responsible for any damage or injury to the persons or things caused or suffered during the execution of the work and shall be made good or compensated at his own cost.
- 5.7. The Contractor shall take all care and precautionary measures for avoiding any kind of damage/accidents in the work site due to any of his reasons. The Contractor shall indemnify the Port against any compensation whatsoever payable to the workmen for accident or loss arising out of and in the course of their employment under this Contract.
- 5.8. The work shall be arranged by the Contractor without causing any damage to Port structures. Any damage or accident caused by the Contractor's operation shall be compensated / made good at Contractor's risk and cost to the satisfaction of the Engineer's Nominee of the works, failing which department will do the rectification work and the cost incurred will be recovered from his bill or from security deposit.

- 5.9. The Contractor shall not construct any structure, even of temporary nature, for any purpose at site, except with the written permission of the Engineer's Nominee of the work and any construction so put up shall be removed by the Contractor whenever the Engineer's Nominee calls upon the Contractor to do so.
- 5.10. The Contractor shall remove all temporary works, clear and make good the site, at his cost to the satisfaction of the Engineer's Nominee before the site is returned to the Port Trust. All materials shall be disposed to any place as pointed out by the Engineer's Nominee of the work and site shall be cleared in every respect at no extra cost after completion of work.
- 5.11. The Contractor shall remove all materials brought to work site / stacked at the work site or anywhere else within the Port area and clear the site at his cost to the full satisfaction of the Engineer's Nominee before the site is returned to the Port Trust. All such materials including debris, tools & plants etc. shall be disposed off to any place as pointed out by the Engineer's Nominee or be taken away from the location and shall be cleared in every respect and to reinstate to its original condition at no extra cost to the Port Trust immediately after completion of the work. In case, any such material is found left in the work site or anywhere in the Port area, rent for the storage space occupied by the Contractor, either for stacking the materials /debris or for areas used for such purpose but not cleared thereafter, will be recovered as per the prevailing Scale of Rate of Cochin Port Trust, for the rent applicable for open storage space for commercial purpose, for the period for which the area had been occupied by the Contractor. In addition to the above, in case the Port requires the area immediately for its use, Port will repossess the land after restoring it to its original condition, material will be confiscated and disposed off at the risk and cost of the Contractor, after issuing two notices giving 15 days' time each for removing the material. All expenses incurred in this shall be recovered by disposing off the material if any confiscated. If any balance amount still remains to be realized that will be recovered from the Contractor by appropriate means.
- 5.12 The Contractor shall observe all safety regulations during the execution of the work. Safety measures, precautions, warning signals etc. shall be taken/provided at the Contractor's cost, as directed by the Engineer-in-Charge of the work. The Contractor shall provide all necessary personnel protection equipments such as helmet, lifeguard, goggles, boots, safety belts etc. to the workmen at his own cost and it shall be the Contractor's responsibility to ensure that they use it while on the work site.
- 5.13 The Contractor shall ensure that no labourers with criminal background are engaged for the work.
- 5.14 The contractor shall take all precautions for not to damage any cables, pipelines etc. passing through the area of work.

- 5.15. The Contractor shall comply with all the provisions of the Indian Workmen's Compensations Act, Public Liability Policy, Provident Fund Regulations, Employees Provident Fund and ESI Act etc. amended from time to time and rules framed there under and other laws affecting the Contract labour that may be brought in to force from time to time.
- 5.16. The contractor shall be registered under EPF and ESI Act and the employees employed under them shall be covered in the EPF and ESI scheme, as applicable under the act.

If the number of employees proposed to be engaged in the work is less than the threshold limit under ESI/EPF act, an undertaking to this effect shall be included in the tender submission.

- 5.17. The Contractor shall provide, at every work place, at which 20 or more women workers are ordinarily employed, crèches of reasonable size and with adequate facility for the use of their children under the age of six years at his risk and cost.
- 5.18 The Contractor shall also be responsible for arranging and carrying out works as mentioned in Clauses 1.1 & 1.2 above.

#### 6. POWER AND WATER

- 6.1 Electric power required for the work can be supplied by the department from the nearest existing line of the Port Trust (CFH Administration) at prevailing rates. The cost of drawing temporary lines/ cables/ providing switches and making connection and metering arrangements etc, shall be borne by the Contractor. If there is any disruption in the power supply due to supply failure/ restrictions imposed by the Kerala State Electricity Board, the department shall not be held responsible and the Contractor has to make suitable alternative arrangements at their cost.
- 6.2 Water required for the work shall be arranged by the Contractor at his own cost.

#### 7. WORKMANSHIP

- 7.1 All the works shall be done strictly according to relevant B.I.S. specifications unless otherwise specified. Whenever special conditions and other specifications deviate from the B.I.S. the former shall prevail.
- 7.2 The whole work shall be completed in a diligent manner within the Contract period and defect or imperfection if any, observed during the Defect Liability Period/ guarantee period the same shall be rectified at Contractor's cost to the full satisfaction of the Engineer's Nominee within the time allowed.
- 7.3 Precautions shall be taken for not to damage cables/ pipe lines etc.

7.4 The work shall be arranged in the order of preference and as directed by the Engineer's Nominee of work.

#### 8. TEMPORARY WORKS

- 8.1 All scaffolding, staging, bracing and other temporary works required for proper execution of the works, shall be provided by the Contractor at his own cost, unless stated otherwise and that should be inclusive of all materials, labour, supervision and other facilities. The layout and details of such temporary works shall have prior approval of the Engineer's Nominee, but the Contractor shall be responsible for proper strength and safety of the same. All temporary works shall be so constructed as not to interfere with any permanent work or with the work of other agencies. If it is necessary to remove any of the temporary works at any time to facilitate execution of works or work by other agencies, such removal and re erection, if required, shall be carried out by the Contractor at the direction of Engineer's Nominee without any delay and any extra cost on this account shall be borne by the Contractor.
- 8.2 On completion of the works, temporary works if any provided by the Contractor shall be removed from the site and the area shall be reinstated to the original condition at his own risk and cost.

#### 9. TIME FOR COMPLETION

- 9.1 The time allowed for carrying out the work as mentioned in the memorandum shall be strictly observed by the Contractor. The work shall throughout the time period be proceeded with diligence, time being deemed to be the essence of the Contract. The number of days lost due to heavy rain shall be certified by the Engineer's Nominee. The Contract period shall be extended for such certified days also without imposing compensation for delayed performance.
- 9.2 The whole work shall be completed in accordance with the provisions under Contract Data or such extended time as may be allowed as per clause 29 of G.C.C.

#### 10. WORKING TIME

The normal working time of the Port Trust is from 8 a.m. to 4.00 p.m. on all weekdays. If the Contractor wishes to carry out the work beyond normal working hours and or on holidays, he should get specific approval from the Engineer's Nominee for the same. Necessary supervision will be arranged by the department and the expenditure to be incurred in this connection will be borne by the department.

#### 11. RATES FOR VARIOUS ITEMS

The rate specified for each item shall be all inclusive value of the finished work, income tax and other taxes but excluding Service Tax.

#### 12. ALTERATIONS / ADDITIONS / OMISSIONS

The quantities given in the bill of quantities (Schedule of items) are only approximate and payment will be made as per actual quantity of work done and rate specified.

#### 13. MEASUREMENT

The quantities shall, unless otherwise stated, be measured in accordance with I.S.1200.

- 14. For levying compensation as per Clause-49 of General Conditions of Contract (GCC), the Employer is not required to have documentary evidence to quantify or prove the losses suffered by the Employer due to delay in completion of work by the Contractor, as per conditions.
- **15.** Clause-25 of GCC- 'Settlement of Disputes and Arbitration' is not applicable in this Contract.
- **16.** Clause-26 of GCC- 'Computerised Measurement Book' is modified to the extent as detailed below.

#### **Measurements of Work Done:**

Executive Engineer (hereinafter called the Engineer's Nominee) shall, except as otherwise provided, as certain and determine by measurement the value in accordance with the Contract of work done.

All measurement of all items having financial value shall be entered in Measurement Book and/or level field book so that a complete record is obtained of all works performed under the Contract.

All measurements and levels shall be taken jointly by the Engineer's Nominee or his authorised representative and by the Contractor or his authorised representative from time to time during the progress of the work and such measurements shall be signed and dated by the Engineer's Nominee and the Contractor or their representatives in token of their acceptance. If the Contractor objects to any of the measurements recorded, a note shall be made to that effect with reason and signed by both the parties.

If for any reason the Contractor or his authorised representative is not available and the work of recording measurements is suspended by the Engineer's Nominee or his representative, the Engineer's Nominee and the Department shall not entertain any claim from Contractor for any loss or damages on this account. If the Contractor or his authorised representative does not remain present at the time of such measurements after the Contractor or his authorised representative has been given a notice in writing three (3) days in advance or fails to countersign or to record objection within a week from the date of the measurement, then such measurements recorded in his absence by the

Engineer's Nominee or his representative shall be deemed to be accepted by the Contractor.

The Contractor shall, without extra charge, provide all assistance with every appliance, labour and other things necessary for measurements and recording levels.

Except where any general or detailed description of the work expressly shows to the contrary, measurements shall be taken in accordance with the procedure set forth in the specifications notwithstanding any provision in the relevant Standard Method of measurement or any general or local custom. In the case of items which are not covered by specifications, measurements shall be taken in accordance with the relevant standard method of measurement issued by the Bureau of Indian Standards and if for any item no such standard is available then a mutually agreed method shall be followed.

The Contractor shall give not less than seven days' notice to the Engineer's Nominee or his authorised representative in charge of the work before covering up or otherwise placing beyond the reach of measurement any work in order that the same may be measured and correct dimensions thereof be taken before the same is covered up or placed beyond the reach of measurement and shall not cover up and place beyond reach of measurement any work without consent in writing of the Engineer's Nominee or his authorised representative in charge of the work who shall within the aforesaid period of seven days inspect the work, and if any work shall be covered up or placed beyond the reach of measurements without such notice having been given or the Engineer's Nominee's consent being obtained in writing the same shall be uncovered at the Contractor's expense, or in default thereof no payment or allowance shall be made for such work or the materials with which the same was executed.

Engineer's Nominee or his authorised representative may cause either themselves or through another officer of the department to check the measurements recorded jointly or otherwise as aforesaid and all provisions stipulated herein above shall be applicable to such checking of measurements or levels.

It is also a term of this Contract that recording of measurements of any item of work in the measurement book and/or its payment in the interim, on account or final bill shall not be considered as conclusive evidence as to the sufficiency of any work or material to which it relates nor shall it relieve the Contractor from liabilities from any over measurement or defects noticed till completion of the defects liability period.

#### 17. Clause 45 and Clause 80 of GCC shall be modified as below;

Clause 45-Rates for items to be inclusive of Taxes The rate quoted by the Contractor shall be inclusive of the cost of provision of plant and equipment, materials, labour, execution, supervision, maintenance, overheads and profits and every incidental and contingent cost and charges whatsoever excluding Goods and Service Tax (GST). GST as may be applicable from time to time shall be shown separately in the invoice. The Employer will perform such

duties in regard to the deduction of such taxes at sources as per applicable law. Any new Taxes, levies, duties imposed after signing the Contract shall be reimbursed by the Employer on production of documentary evidence. The invoice to be submitted by the Contractor should include the GST Registration Number of the Contractor as well as the Employer.

Clause 80-Taxes and Duties Income Tax The Contractor and his staff shall be responsible for payment of all personal income taxes to the concerned authorities as per the law in force from time to time. Deduction of Income Tax shall be made by the Employer from each certificate of payment to the Contractor at the rate of 2% plus surcharge or such other rates as may be specified by the Central Government from time to time, on the gross amount of the Contractor's bill for payment. The Contractor shall comply all the GST Regulations viz. timely uploading of bills, issue of debit/ credit notes etc.

- 18. Sub clause **43.2** under **Clause 43:Payments,....** in GCC 2016 stands amended as given below:
  - 43.2 Payment of bills for Civil Works shall be regulated as detailed hereunder:
    - 43.2.1 Any Interim/Final bill which is incomplete in any respect shall be returned to the Contractor within 5 days of date of submission of bill to the Engineer or his Nominee.
    - 43.2.2 Interim bills shall be paid within 21 days of date of submission of bills in full shape, by the Contractor, as detailed below.
    - 43.2.3 Clarifications/corrections if any required on an Interim bill submitted, shall be sought from the Contractor within 4 days of submission of the bill and also, all such clarifications/corrections required shall be sought at one go except in exceptional circumstances. The Contractor shall submit the clarifications including carrying out corrections in the bill, if required, within 4 days thereafter. The clarified / corrected bill shall be verified and forwarded to Finance Department within the next 4 days. Clarifications if any required by the Finance Department shall be sought within 3 days and the Engineer/Nominee shall clear it on top priority within the next 3 days and, finally, the bill shall be paid to the Contractor within 3 days thereafter, i.e., within a total 21 days of date of submission of bills in full shape, as indicated above.

- 43.2.4 However, on request by the Contractor, 75% of the bill amount shall be paid within 7 days of submission of the bill. Balance amount of the verified bill shall be paid within 21 days of the submission of the bill, on completion of all contractual requirements as brought out at sub clause 43.2.3. above.
- 43.2.5 Final bill shall be paid within 3 months of issue of Taking Over Certificate by the Engineer / Nominee, as detailed below.
- 43.2.6 The Contractor shall submit the Final bill to the Engineer / Nominee within 20 days of issue of Taking Over Certificate by the Engineer / Nominee. The bill shall be checked and all clarifications/corrections required on the bill submitted, shall be sought from the Contractor within 15 days thereafter. The Contractor shall submit the clarifications including carrying out corrections in the bill, if required, within the next 10 days. The clarified / corrected bill shall be verified and forwarded to Finance Department within the next 15 days. Thereafter, clarifications if any required by the Finance Department shall be sought within 10 days and the Engineer/Nominee shall clear it on top priority within the next 10 days and, finally, the bill shall be paid to the Contractor within 10 days thereafter, i.e., within a total 3 months of issue of Taking Over Certificate by the Engineer / Nominee, as indicated above.
- 43.2.7 However, on request by the Contractor, 50% of the final bill amount shall be paid within 7 days of submission of the bill, which will be adjusted against the final bill payment, on completion of all contractual requirements as brought out at sub clause 43.2.6. above.

SIGNATURE OF TENDERER

#### 6. DETAILED SPECIFICATIONS FOR MATERIALS TO BE USED ON WORK

#### 1. GENERAL

- 1.1. Except where otherwise specified or authorized by the Engineer-in-Charge, materials supplied by the contractor shall conform to the latest edition of the Indian Standard Specifications and code of practices published by the Indian Standard Institution. Samples of materials to be supplied by the contractor shall be shown to the Engineer-in-Charge sufficiently in advance for approval of its quality for use on the work.
- 1.2. All materials supplied shall be stored appropriately to prevent deterioration/damage from any cause what so ever and to the entire satisfaction of the Engineer-in Charge.
- 1.3. The materials required for the work shall be brought to the site and stacked at the places shown by the Engineer-in-Charge and the same shall be got approved for use in work sufficiently advance so that the progress of the work is not affected by the supply of materials.
- 1.4. Payment for the materials supplied, shall be given only after they are used on the work.
- 1.5. Tolls are payable by the Contractor as per rules for vehicles using the Port's road for supplying the materials.

#### 2. AGGREGATES FOR CONCRET

- 2.1 Aggregates (fine and coarse) for concrete shall comply with the requirements of I.S. 383 'Specifications for coarse and fine aggregate from natural sources for concrete'. Aggregate shall be obtained from sources approved by the Engineer-in-Charge. Aggregates, which are not perfectly clean, shall be washed in clean water to the entire satisfaction of the Engineer-in-Charge.
- 2.2 The fine aggregate shall be clean, hard, durable, uncoated, dry and free from injurious, soft or flaky pieces and organic or other deleterious substances.
- 2.3 Each type of aggregate shall be stored separately for the approval of Engineer-in-Charge. Wet aggregate delivered at the site shall be kept in storage for at least 24 hours to ensure adequate drainage before being used for concreting.
- 2.4 Contractor shall maintain at site at all times such quantities of each type of aggregate as are considered by the Engineer-in-Charge to be sufficient to ensure continuity of work.

#### 3. CEMENT

3.1 Quality of cement used for the work shall be 43 grade ordinary Portland cement conforming to I.S. 8112 or 53 grade ordinary Portland cement conforming to I.S. 12269 or Pozzolona cement conforming to I.S. 1489 unless otherwise approved by the Engineer-in-Charge.

- 3.2 The cement required for the work will have to be procured by the contractor and shall comply with the relevant IS. As far as possible, the cement required for the work will have to be procured from the government agencies. The cement shall, if required by the Chief Engineer / Engineer-in-Charge, be tested and analyzed by an independent analyst at the Contractor's cost and result produced to the Engineer-in-Charge.
- 3.3 Supply of cement shall be taken in 50kg bags bearing manufacture's name and ISI marking. Samples of cement arranged by the Contractor shall be taken by the Engineer-in-Charge and got tested in accordance with provisions of relevant B.I.S codes. In case, test results indicate that the cement arranged by the Contractor does not conform to the relevant B.I.S codes, the same shall stand rejected and shall be removed from the site by the Contractor at his own cost within a week's time of written order from the Engineer-in-Charge to do so.
- 3.4 A cement godown of adequate capacity as directed by the Engineer-in-Charge shall be constructed by the Contractors at the site of the work for which no extra payment shall be made. Double lock provision shall be made to the door of the cement godown. The key of one lock shall remain with the Engineer-in-Charge or his authorized representative and the key of the other lock shall remain with the Contractor. The Contractor shall be responsible for the watch and ward and safety of the cement godown. The Contractor shall facilitate the inspection of the cement godown by the Engineer-in-Charge.
- 3.5 The cement brought to the site and cement remaining unused after completion of work shall not be removed from the site without written permission from /of the Engineer-in-Charge.
- 3.6 The cement shall be stored in a weather proof building with facilities for inspection.
- 3.7 The Contractor shall maintain a cement register showing dates of receipt and issue, quantities used daily and balance which shall be accessible to the Engineer-in-Charge.

#### 4. STEEL REINFORCEMENT

- 4.1 The reinforcement steel used for the work will have to be procured by the contractor and shall be HYSD bars of Fe550 /Fe 500 / Fe415 grade conforming to IS:1786 unless otherwise approved by the Engineer-in-Charge.
- 4.2 As far as possible, the reinforcement steel required for the work shall be procured from Steel Authority of India or Rashtriya Isbat Nigam Ltd. The reinforcement steel can also be procured from the firms TATA Iron & Steel, Jindal Steel & Power Ltd and Shyam Steel Industries, Durgapur for use in the work subject to production of valid license certificate from BIS. In case steel is not available from the above sources, the contractor shall obtain specific

- approval from the Engineer-in-Charge well in advance for purchase of steel from other sources.
- 4.3 The contractor shall have to obtain and furnish test certificates to the Engineer-in-Charge in respect of all supplies of steel brought by him to the site of work. Samples shall also be taken and got tested by the Engineer-in-Charge as per provisions in this regard in relevant BIS codes. In case the test results indicate that the steel arranged by the Contractor does not conform to BIS codes, the same shall stand rejected and shall be removed from the site of work by the Contractor at his cost within a week's time of written orders from the Engineer-in-Charge to do so.
- 4.4 The steel reinforcement shall be brought to the site in bulk supply of 10 tonnes or more or as decided by the Engineer-in-Charge.
- 4.5 The steel reinforcement shall be stored by the contractor at site of work in such a way as to prevent distortion and corrosion and nothing extra shall be paid on this account. Bars of different sizes and lengths shall be stored separately to facilitate easy counting and checking.
- 4.6 For checking nominal mass, tensile strength, bend test etc., specimen of sufficient length as per IS:432/ IS:1608/ IS:1599 or as specified by the Engineer-in-Charge shall be cut from each size of the bar at random at frequency not less than the specified below.

| Size of bar        | For consignment below 100 tonnes              | For consignment over 100 tonnes               |
|--------------------|---|---|
| Under 10 mm<br>dia | One sample for each 25 tonnes or part thereof | One sample for each 40 tonnes or part thereof |
| 10 mm to 16 mm dia | One sample for each 35 tonnes or part thereof | One sample for each 45 tonnes or part thereof |
| Over 16 mm dia     | One sample for each 45 tonnes or part thereof | One sample for each 50 tonnes or part thereof |

- 4.7 The contractor shall supply free of charge the steel required for testing. The cost of tests shall be borne by the Contractor.
- 4.8 Steel brought to site and steel remaining unused shall not be removed from site without the written permission of the Engineer-in-Charge.

#### 5. WATER

- 5.1 Clean fresh water free from oils, acids, alkalies, salt, sugar, organic materials or other harmful materials shall be used. The water used shall comply with clause 5.4 of I.S. 456-2000. Potable water is generally considered good.
- 5.2 Cochin Port Trust will not provide/supply water for the work. Water has to

- be arranged by the Contractor himself for the construction works if necessary at his own risk and cost.
- 5.3 Samples of water arranged by the Contractor shall be taken by the Engineer in Charge and got tested in accordance with the provisions of relevant BIS codes. In case test results indicate that the water arranged by the Contractor does not conform to the relevant BIS codes, the same shall not be used for any works. The cost of tests shall be borne by the Contractor.

#### 6. SAND FOR MAKING MORTAR/PLASTERING WORK

6.1 Sand used for making mortar shall conform to IS 2116. Sand used for plastering shall conform to IS: 1542.

#### 7. <u>6 MM SIZE AGGREGATE</u>

7.1 6mm size graded aggregate conforming to IS 383 shall be used which are not perfectly clean shall be washed in clean water to the entire satisfaction of the Engineer-in-Charge.

#### 8. BRICKS

- 8.1 Bricks shall suit the required wall thickness and shall conform to IS 1077, Class 50-B and shall have a minimum compressive strength of 50 kg/sq.cm and shall not absorb water more than 20% of its dry weight, when soaked in cold water for 24 hours. The tolerance limit shall be 6% for absorption.
- 8.2 In case where locally available bricks do not meet the standards, contractor shall carry out all the tests specified as above in IS: 1077 on the bricks and submit the test report to Engineer–in–Charge, who will take a final decision on the use of the bricks which shall be binding.

#### 9. VITRIFIED FLOORING / SKIRTING TILES

- 9.1 Tiles shall be of approved premium quality, Johnson or Khajaria or Asian or Somany or Orient Bell make and of approved colour and shade. The tiles shall be generally conforming to IS:13756/ IS:15622 with water absorption less than 0.08% and having modulus of rupture greater than 500kg/sq.cm & modulus hardness 8.0. The tiles shall be flat, true to shape and free from cracks, crazing spots, clipped edged and corners. The tiles shall be of 600mm x 600mm size or nearest available higher size and shall have minimum thickness of 10mm.
- 9.2 The top surface of the tiles shall be glossy/ mat finish / antiskid as specified in the Schedule of quantities and as approved by the Engineer-in-Charge. The underside of the tiles shall be completely free from glazing in order to adhere properly to the base.
- 9.3 Manufactures test Certificate for water absorption, breaking strength, abrasion

resistance and crazing has to be produced by the contractor.

#### 10. CERAMIC TILES FOR FLOORING

- 10.1 Ceramic tiles shall be of approved premium quality, Johnson or Khajaria or Nitco or Asian or Orient Bell make and of approved colour and shade. The tiles shall generally conform to IS:15622 and shall be conforming to Group B II. The abrasion resistance of the tiles shall be of Class IV and above. They shall be flat, true to shape and free from cracks, crazing spots, clipped edged and corners. The flooring tiles shall be of antiskid type tiles and shall be of 300mm x 300mm size or nearest available higher size with thickness not less than 8mm.
- 10.2 The top surface of the tiles shall be antiskid as specified in the Schedule of quantities and as approved by the Engineer-in-Charge. The underside of the tiles shall be completely free from glazing in order to adhere properly to the base.
- 10.3 Manufactures test Certificate for water absorption, breaking strength, abrasion resistance and crazing has to be produced by the contractor.

#### 11. <u>CERAMIC TILES FOR SKIRTING/ DADOOING</u>

- 11.1 Ceramic tiles shall be of approved premium quality, Johnson or Khajaria or Nitco or Orient Bell make, luster printed and of approved colour and shade. The tiles shall generally conform to IS 15622 and shall be conforming to Group B III or higher quality. They shall be flat, true to shape and free from cracks, crazing spots, clipped edged and corners. The glazing shall be of uniform shade. The tiles shall be of 300mm x 200mm size or nearest available higher size. It shall have thickness not less than 6mm.
- 11.2 The top surface of the tiles shall be glossy as approved by the Engineer-in-Charge. The underside of the tiles shall be completely free from glazing in order to adhere properly to the base.
- 11.3 Tests like water absorption, impact strength and crazing has to be carried out for the tiles and certificates shall be produced. The cost towards these tests has to be borne by the contractor.

# 12. <u>CHLORINATED POLYVINYL CHLORIDE (CPVC) PIPES (FOR WATER LINE)</u>

12.1 CPVC pipes & fittings used in hot & cold potable water distribution system shall conform to requirement of IS:15778. The material from which the pipe is produced shall consist of chlorinated polyvinyl chlorides. The polymer from which the pipe compounds are to be manufactured shall have chlorine content not less than 66.5%.

12.2 The internal and external surfaces of the pipe shall be smooth, clean and free from grooving and other defects. The pipes shall not have any detrimental effect on the composition of the water flowing through it.

#### 13. <u>CPVC FITTINGS (FOR WATER LINE)</u>

13.1 All fittings shall be of injection moulded CPVC socket type with BIS's certification mark and designated by the diameters of their sockets. All fittings shall in all respects comply with IS:7834 (Part I-VIII).

#### 14. WASH BASIN

- 14.1 Wash basin shall be of White Vitreous wash basin of 1000 x 480 x160 mm size Pastel brand (No.91037) of "Hindware" or equivalent approved make of "Kohler/ Jaquar" with single tap hole to suit the sensor tap. The inside surface of the basin shall have uniform slope towards the waste hole.
- 14.2 Galvanized rag bolts with nut having suitable diameter and length as approved by the Engineer charge shall be used for fixing the wash basin.
- 14.3 Waste fittings for wash basin shall be of brass and shall conform to IS:2963. The fitting shall be chromium plated.

#### 15. GLASS

15.1 The glass to be used on the work shall be of good quality of make "Saint Gobain" or "Modiguard" conforming to IS:2835 and free from defects scratches etc. The thickness of glass shall be as specified in the Schedule of quantities.

#### 16. WATER THINNABLE CEMENT PRIMER

16.1 The primer used for the work shall be Silicon based primer, manufactured by Asian/Nerolac/Berger/Nitco of premium quality.

#### 17. ACRYLIC EMULSION PAINT EXTERIOR/INTERIOR

17.1 The weather proof exterior acrylic emulsion paint shall be of approved premium quality either "Weather coat" by Berger or Nerolac Excel or "Weather shield" by ICI Dulux or Snowcryl XT-premium by Snowcem India Ltd. or Jotun Paints/ Asian paints. The interior acrylic emulsion paint shall be of approved premium quality either manufactured by Berger or Dulux or Nicholson or Jotun Paints/ Asian paints. The coverage shall conform to the manufacture's specification. The colour/ shade shall be as per direction of the Engineer-in-Charge.

#### 18. SAMPLING AND TESTING OF MATERIALS

- 18.1. Sampling and testing of the material supplied by the contractor for use on the Work shall be done as per the provisions of the relevant BIS codes/specifications. In the absence of BIS specification in a particular case, the sampling and testing shall be done as directed by the Engineer-in-Charge as per sound engineering practice. Material conforming to the specifications and approved by the Engineer-in-Charge shall only be used by the Contractor.
- 18.2. All the sampling and testing shall be done at the Contractor's cost.

SIGNATURE OF CONTRACTOR

#### 7. DETAILED SPECIFICATIONS FOR ITEMS OF WORKS

#### 1. GENERAL

Except where otherwise specified or authorized by the Engineer-in-Charge, all items of works executed by the contractor shall conform to the latest edition of the Bureau of Indian Standard Specifications and code of practices published by the B.I.S. Where no such specifications or code of practice exists the latest B.S.S. codes of practice or any other equivalent / standard code of practice shall also be considered for adoption. The tenderer while indicating any such specifications shall enclose the full set of the publication so referred and not in extracts. Photostats / Xerox copies in duplicate shall be forwarded which shall not be returned to the contractor. In absence of any specification, the department deserves the right to adopt trade specifications and/or sound engineering practices for the specialized work as may be decided by the Engineer-in-Charge which shall be final, conclusive and binding on the contractor.

#### 2. <u>DISMANTLING/ DEMOLISHING WORKS</u>

- 2.1 The tenderer shall inspect the site and carry out the required investigation by himself about the present position and condition of the existing structures and assess the difficulties and the work involved in its dismantling and removal. It will be deemed that the tenderer has satisfied himself the condition of the structure and the nature of the work involved for the dismantling and removal and estimated its cost accordingly and port will be in no way responsible for the lack of such knowledge and also consequences thereof to the tenderer. The dismantling shall be done carefully without causing any damage to the remaining portions / structure.
- 2.2 Old Brick masonry/ PCC/ RCC works/Aluminium/ Gypsum partition, doors etc., are to be dismantled as per the direction of Engineer-in-charge. All the dismantled usable materials shall be stacked at the area pointed out by the Engineer –in –charge and all unusable materials shall be disposed by the contractor.
- 2.3 All the dismantling works shall be done carefully without causing any damage to the adjacent portion/existing structure. The unserviceable dismantled / cut materials shall be disposed off within 6kms of the work site and levelled as directed by the Engineer-in-Charge.

2.4

#### 3. PLAIN / REINFORCED CEMENT CONCRETE

#### 3.1 **GENERAL**

The concrete used for all works, concreting procedure etc. shall be in accordance with I.S. 456–2000.

#### 3.2 **CONCRETE MIX**

For Plain cement concrete, nominal mix shall be used unless otherwise specified in the schedule.

#### 3.2.1. **NOMINAL MIX**

For nominal mix concrete, proportion of fine aggregate to coarse aggregate shall be 1:2 by volume. The minimum cement content per cubic metre of nominal mix concrete shall be as given below.

| Sl.<br>No | Type of Concrete   | Cement content Per<br>Cu. M |
|-----------|--|-----------------------------|
| 1         | Cement concrete 1:2:4 (1 cement: 2 sand: 4, 20 mm size graded metal) | 320 Kg.                     |
| 2         | M-30 Grade   | 340 Kg                      |

3.2.2. For all grades of nominal mix concrete the requirement of water cement ratio shall be as per IS:456-2000

#### 3.3 SIZE OF COARSE AGGREGATE

3.3.1 For all concrete 20 mm size graded aggregate shall be used unless otherwise specified.

#### 3.4 PROVIDING REINFORCED CEMENT CONCRETE

#### **3.4.1** General

- 3.4.1.1 The concrete used for all works, concreting procedure etc. shall be in accordance with IS:456-2000. The concrete mix shall be of 1:1.50:3 grade using 20mm size graded aggregate metal with a cement content of not less than 320kg/m3 and water cement ratio not exceeding 0.50
- 3.4.1.2 Designed concrete mix shall be used for the work. For this purpose, the contractor shall make calculations and carry out all the tests at his cost to determine the proportion by weight of cement, aggregates, admixtures and water necessary to produce concrete having required strength, prior to commencement of works. The contractor shall submit all the particulars of the design mix to be used for the work to the Engineer-in-Charge for approval as per clause 1.2.3.4 above. The quality of concrete shall be assured by conducting the required tests so as to meet the requirements as per BIS.
- **3.4.1.3** The concrete for slabs shall be of pre-cast. Concrete for kerbs shall be of castin-situ.

#### 3.4.2 Assembly of reinforcement for Reinforced Cement Concrete.

3.4.2.1 The contractor shall, when ordered, submit to the Engineer-in-Charge the detailed bar bending schedule for his scrutiny and approval sufficiently in advance (about four weeks) of the due date of commencement of the relevant items of works. While working out the bar bending schedule, the contractor

shall ascertain the length of bars likely to be made available to him and the schedule shall be so made, keeping the wastage/ cut bits of bars to bare minimum without hampering technical requirements. If the size of the steel bars specified in the drawing or schedule is not available, the nearest size available shall be used. Revised drawing shall be issued to the contractor substituting the new size of reinforcement and bar bending schedule shall be prepared by the contractor accordingly. No extra payment shall be made to the contractor for making this substitution. The fabrication of reinforcement shall commence only after the bar bending schedule is approved by the Engineer-in-Charge.

- 3.4.2.2 Reinforcement shall be cut to the exact length and made truly straight and then bent to the exact shape and dimensions as indicated in the drawings. The bending and fixing of bars shall be done in accordance with IS:2502 unless otherwise specified.
- 3.4.2.3 All cut bits of steel are the property of the contractor. However, the contractor can dispose them off only with the permission in writing of the Engineer-in-Charge. If the department requires the cut lengths, they are to be handed over to the department and will be paid for at the rates at which they were purchased by the contractor.
- 3.4.2.4 The reinforcement shall be cleaned by wire brush etc. to remove oil, grease, loose mill scale, loose rust or other deleterious matter that may reduce or destroy bond etc. before tying in position and also immediately before placing the concrete.
- 3.4.2.5 All reinforcement shall be placed and maintained in accordance with the drawings. Tolerance on placing of reinforcement shall be in accordance with clause 12.3 of IS:456-2000. Bolts, nuts, washers and rivets etc. required for complete erection of reinforcement and keeping in position shall be supplied by the contractor at his own cost.

#### 3.4.3 FORM WORK

3.4.3.1 The form work shall be designed and constructed to the shape, lines and dimensions shown in the drawings within the tolerance limit and specified in clause 11.1 of IS:456-2000. Joints of the form works shall be made water tight by providing suitable beadings / gasket as approved by the Engineer-in-Charge. All rubbish, particularly chippings, shaving and saw dust, shall be removed from the interior of the forms before the concrete is placed and the form work in contact with the concrete shall be cleaned and thoroughly wetted or treated with an approved composition. Care shall be taken that such approved composition is kept out of contact with the reinforcement.

#### 3.4.4 MIXING OF CONCRETE

3.4.4.1 Concrete shall be mixed in a drum or pan type batch mixer, the type and

capacity of which is to be approved by the Engineer-in-Charge. Time allowed for mixing, after all ingredients have been placed in the mixers shall not be less than two minutes. If there is segregation after unloading from the mixer, the concrete should be remixed.

### 3.4.5 TRANSPORTING, PLACING, COMPACTING AND CURING OF CONCRETE

- 3.4.5.1 Transporting placing, compacting and curing of concrete shall be as per clause 13 of IS: 456-2000.
- 3.4.5.2 Concrete shall be transported from the mixer to the worksite as rapidly as possible which will prevent the segregation or loss of any ingredient, and for maintaining the workability.
- 3.4.5.3 The concrete shall be placed and compacted before setting commences and should not be subsequently disturbed. Care should be taken to avoid displacement of reinforcement or movement of formwork.
- 3.4.5.4 All concrete shall be vibrated unless otherwise specified or approved by the Engineer-in-Charge and such vibrating shall be as required by the Engineer-in-Charge. The mechanical vibrators complying with IS: 2505, IS: 2506 or IS: 4656 shall be used for compacting concrete. All vibrations shall be carried out to a plan approved by the Engineer-in-Charge. No workman shall be allowed to operate the vibrator without having received instructions and training in its use. Care must be taken to avoid segregation and excessive vibration.
- 3.4.5.5 Concreting shall be carried out continuously upto construction joints, the positions and arrangement of which shall be as directed by the Engineer-in-Charge. When the work has to be resumed the construction joints shall be prepared in accordance with clause 13.4 of I.S: 456-2000.
- 3.4.5.6 Unless otherwise specified, all concrete shall be kept continuously in a damp condition by ponding or by covering with a layer of sacking, canvas, hessian or similar materials with fresh water for not less than 7 days after laying the concrete. If curing is not done properly the department will be at liberty to engage labour for curing and the expenditure incurred will be recovered from the Contractor's bill. The decision of the Engineer-in-Charge will be final on this.
- 3.4.5.7 Stripping time for the form work shall be as stipulated in clause 11.3 of IS: 456-2000. Any impression, fins etc. that may occur from the form work shall be removed and treated with cement mortar 1:1.5 (1 cement: 1.5 sand).
- 3.4.5.8 Contractor shall arrange to fix any fixtures wherever necessary while doing concreting work without any extra cost. Cost of fixtures will be paid separately, if it is provided by the Contractor.
- 3.4.5.9 The unit rate quoted by the tenderer shall be for the finished work and deemed to include cost of all materials and labour, form work, provision of holes,

recess, other contingent items etc. required for the completion of work as specified etc.

#### 4. BRICK MASONRY

- 4.1 Brick masonry shall conform to IS: 2212. All bricks shall be thoroughly soaked in water for at least 6 hours before use. Brickwork shall not be raised more than 14 courses per day.
- 4.2 The grade of mortar shall be as specified in the Schedule of Quantities.
- 4.3 Joints shall be restricted to a thickness of 10mm unless otherwise required and shall be squarely raked to a depth of 12mm while the mortar is still wet and brushed.
- 4.4 Curing shall be done for 7 days.
- 4.5 Payment for brick masonry shall be made on cubic metre basis irrespective of thickness. The rate shall include all labour and materials including scaffolding.

#### 5. CEMENT PLASTERING

- 5.1 Cement plastering shall be with the grade of mortar and of thickness specified in the schedule. The surface to be plastered shall be thoroughly cleaned and kept wet for 4 hours before plastering.
- 5.2 All the corners shall be rounded off to a radius of 25 mm unless otherwise specified.
- 5.3 Where smooth finishing is specified in the schedule the plastering shall be floated over with neat cement slurry using 2.2 kg of cement per square metre immediately after the final coat of plastering and rate quoted for plastering shall include cost of this finishing work.
- 5.4 The plastered surface on which glazed tiles or other similar type of finishing are to be provided subsequently shall not be finished smooth but shall be scarified for forming a base for providing the final surface finish as required.
- 5.5 The surface shall be cured for 7 days.
- 5.6 The rate shall include all labour and materials including scaffolding, plastering of jambs, sills, soffits or opening, curing etc. complete. required for completion of work. Measurement of the work under this head shall be made on the basis of the area of work done.

#### 6. PROVIDING CERAMIC TILE DADOOING

6.1 For dadooing, the glazed tiles shall be set in cement mortar 1:3 (1 cement: 3 sand) of average 12mm thick laid to required level. Before laying cement mortar, the surface shall be scrubbed with wire brush, all loose particles, foreign matters etc. shall be removed and the surface shall be made clean. Any undulations shall be chipped off and made good. The surface thus

prepared shall be wetted and smeared with a coat of cement slurry using cement at the rate of 2.2 kg/m2 of area just before the application of the mortar, so as to get good bond between base course concrete and plastering. The plastered surface shall be scarified so as to fix the tiles. Ceramic tiles shall be joint free. Border tiles of approved design shall be provided.

- 6.2 The plastered and scarified surface shall be wetted and neat cement slurry of honey like consistency using cement at the rate of 3.30kg/m2 shall be smeared on the surface just before fixing the tiles. The tiles shall be laid over the slurry to the correct level and alignment with minimum joint thickness. The joints shall be raked and pointed with tile jointing powder of same colour as tiles. Finally the surface shall be cleaned with oxalic acid.
- All the exterior corners of columns, walls etc. to be provided with PVC corner beading of approved quality and colour of tiles.
- Measurement of the work under this head, including scarified plastered surface and smearing with cement slurry, shall be made on the basis of the area of work done and rate quoted shall include the cost of all labour and materials providing border tiles, scaffolding etc. required for completion of work.

#### 7. PROVIDING AND LAYING WATER SUPPLY LINES

#### 7.1 General

All the pipes of different diameters and fittings shall be conforming to IS: 15778. The rate quoted shall include cost of all specials like bends, tees, reducers etc., cost of burying or fixing on walls using all fittings as the case may be etc. complete, but excluding cost of taps, valves etc.

## 7.2 PROVIDING AND LAYING OF PIPES FOR EXTERNAL WATER SUPPLY WORKS

#### 7.2.1 Transporting

Pipes, fittings and valves etc. shall be transported from the stacking place to the worksite with sufficient care to avoid damage to them.

#### 7.2.2 Other materials to be made available by the contractor

All other materials except those supplied under specific items in the schedule, required for jointing and laying pipes and fixing valves, including rubber gasket, lead, spun yarn, solvent cement etc. shall be brought by the contractor at his own cost.

#### 7.2.3 **Jointing of CPVC pipes**

Jointing of CPVC pipes shall be done with IS:15778, solvent welded joint shall be used for jointing of CPVC pipes. Solvent welded joint shall be achieved by non-heat application method. Solvent cement used for the joint shall be fully recommended by the manufacturer.

#### 7.2.4 Testing of pipelines for leakage test

The leakage test shall be conducted at a test pressure of 12.5 kg./cm<sup>2</sup> for a duration of 2 hours or as directed by the Engineer-in-Charge for duration of 2 hours. No pipe installation shall be accepted until the leakage per hour in cubic centimeter is less than the quantity (Q) determined by the formula

$$Q = \underline{N \times D \times \sqrt{P}}$$

Where Q = Allowable leakage in cm<sup>3</sup> / hour,

N = No. of joints in the length of the pipeline tested,

D = Diameter of pipe in mm

and  $P = \text{Test pressure during the leakage test in kg/cm}^2$ .

#### 7.2.5 Fixing of valves and fittings

Fixing of valves and fittings shall form part of laying the pipeline as directed by the Engineer-in-Charge.

#### **7.2.6 Payment**

Payment shall be done on running meter basis measured center line length including all the fittings, valves, bolts, nuts etc. No separate payment shall be made for fixing fittings, valves etc. for completing the work to the full satisfaction. The rate quoted shall include the cost of all specials like bends, 'tee's, reducers etc. and materials like rubber gasket, lead, spun yarn, solvent cement, bolts, nuts etc. to be made available by the contractor for jointing pipes, providing suitable connections to the existing delivery line and testing the line as aforesaid.

## 7.3 PROVIDING AND LAYING OF PIPES FOR INTERNAL WATER SUPPLY WORKS

- 7.3.1 The CPVC pipes except installing through ducts, shafts etc shall be concealed in wall. The pipes and fittings are to be pressure tested prior to concealing the chases. The alignment of fittings and pipes shall be done correctly. Do not use nails for holding pipes in the chases.
- 7.3.2 The pipes shall be laid and properly clamped to wooden / fibre plugs embedded on the wall with CPVC clips. Horizontal pipes shall be supported with clamps at spacing not more than 1m center to center. For vertical pipes spacing may be increased by 50%. The pipes shall be aligned properly before fixing them on plugs with clamps. Even if the plugs are fixed using a plumb line the pipe shall also be checked for alignment before clamping.
- 7.3.3 All pipes exposed to sunlight shall be painted with a water based acrylic paint emulsion to enhance UV protection.

7.3.4 Connection to bib tap / stop valve shall be done by means of GI adapter of approved quality and make or as directed by the Engineer-in-Charge.

#### 7.3.5 **Payment**

Payment shall be done on running meter basis measured center line length including all the fittings, valves, bolts, nuts etc. No separate payment shall be made for fixing fittings, valves etc. for completing the work to the full satisfaction. The rate quoted shall include the cost of fittings like 'tee's, bends, reducers etc. and materials like solvent cement, bolts, nuts, rubber gasket etc. to be made available by the contractor for jointing pipes etc.

#### 8. PROVIDING AND FIXING URINAL

- 8.1 Fixing urinal shall consist of a wall urinal, an automatic flushing cistern of 5 litres and waste pipes etc. Waste pipe shall be of 32mm nominal bore.
- 8.2 Urinal shall be fixed in position by using wooden plugs and screws. The size of wooden plugs shall be 50mmx50mm at base, tapering to 38mmx38mm at top and length 5cm. These shall be fixed to the wall in cement mortar 1:3. After the flange is fixed in the wall, the mortar shall be cured till it is set.
- 8.3 Each urinal shall be connected to 32mm dia. Waste pipe which shall discharge in to the channel or a floor trap. The connection between the urinal and flush or waste pipe shall be made by means of putty or white lead mixed with chopped hemp. The unit rate quoted shall also include supply and fixing 12mm CP brass stop cock etc. complete.

#### 9. PROVIDING AND FIXING WASH HAND BASIN

9.1 Washbasin shall be fixed over on galvanized iron rag bolt, embeded in M-15 grade cement concrete in wall. Each basin shall be provided with 32mm dia chromium plated (CP) waste coupling and a 32mm dia PVC waste pipe and one number approved quality CP pillar tap. The cast iron brackets shall be painted with one coat of primer and two coats of synthetic enamel paint. The work shall be carried out as per the directions of the Engineer-in-charge. Water connections shall be done under separate item.

#### 10. WATER THINNABLE PRIMER COAT

10.1 Primer coat shall be preferably applied by brushing and not by spraying.

#### 10.2 **Preparation of the Surface**

The surface shall be thoroughly cleaned of dust, old white or colour wash by washing and scrubbing. The surface shall then be allowed to dry for at least 48 hours. It shall then be sand papered to give a smooth and even surface. Any unevenness shall be made good by applying Putty made of Plaster of Paris mixed with water, on the entire surface including filling up the

undulations and then sand papering the same after it is dry.

#### 10.3 **Application**

The water thinnable primer shall be applied with a brush on the clean dry and smooth surface. Horizontal strokes shall be given first and vertical strokes shall be applied immediately afterwards. This entire operation will constitute one coat. The surface shall be finished as uniformly as possible leaving no brush marks. It shall be allowed to dry for at least 48 hours, before emulsion Paint is applied.

Measurements of the work under this head shall be made on the basis of the area work done and the rate quoted shall include the cost of labour, materials scaffoldings etc. required for the completion of the work.

# 11. PROVIDING AND APPLYING PREMIUM ACRYLIC EMULSION EXTERIOR/INTERIOR PAINT TWO COATS.

- 11.1 The weather proof exterior acrylic emulsion paint shall be of approved good quality either "Weather coat " by Berger or Nerolac Excel or "Weather shield" by ICI Dulux or Snowcryl XT-premium by Snowcem India Ltd. The interior acrylic emulsion paint shall be of approved good quality either manufactured by Berger or Dulux or Nicholson. The coverage shall conform to the manufacture's specification.
- 11.2 Before applying the Interior/Exterior Emulsion Paint, the surface shall be thoroughly cleaned of dust and then be sand papered to give a smooth and even surface. Any unevenness shall be make good by applying Putty made of Plaster of Paris mixed with water on the entire surface including filling up the undulation and then sand papering the same after it is dry. Over the prepared surface one coat of Interior Emulsion Paint shall be applied with hand brush in horizontal stroke followed immediately by a vertical one which together shall constitute one coat (1st coat).
- 11.3 After the 1st coat has dried for at least 48 hours, the finishing coat of Interior Emulsion Paint shall be applied as instructed by the Engineer-in-Charge with hand brush in horizontal stroke followed immediately by a vertical one which together shall constitute one coat.
- Measurements of the work under this head shall be made on the basis of the area of work done and the rate quoted shall include the cost of labour, materials scaffoldings etc. required for the completion of the work.

SIGNATURE OF TENDERER